

(12) UK Patent Application (19) GB (11) 2 358 438 (13) A

(43) Date of A Publication 25.07.2001

(21) Application No 0001150.2

(22) Date of Filing 18.01.2000

(71) Applicant(s)
Air Squared Inc
(Incorporated in USA - Ohio)
7014 Rock Springs Drive, Hamilton, Ohio 45011,
United States of America

(72) Inventor(s)
Robert W Shaffer

(74) Agent and/or Address for Service
Edward Evans & Co
Clifford's Inn, Fetter Lane, LONDON, EC4A 1BX,
United Kingdom

(51) INT CL⁷
F04C 18/02

(52) UK CL (Edition S)
F1F FD FEQ FEW F1A7

(56) Documents Cited
GB 2002455 A EP 0728947 A1 US 4477238 A
US 4457674 A

(58) Field of Search
UK CL (Edition R) F1F FAA FD FEQ FEW FEW
INT CL⁷ F01C 1/02 , F04C 2/02 18/02
Online databases: EPODOC, JAPIO, WPI

(54) Abstract Title
Multi-stage scroll pump or compressor

(57) A multi-stage scroll compressor, or vacuum pump, has a housing which encloses fixed and orbiting scroll plates, each having a continuous involute wrap 109, 111 of constant width and pitch. Each wrap 109, 111 has an outer section 109a, 111a which is at a different height (ie either taller or shorter) than an inner section 109b, 111b, providing different percentage changes in pressure across chambers defined by the outer and inner wraps. An inlet port 121 functions as an inlet to the outer chamber, a mid-port 122 is both the outlet to the outer chamber and an inlet to the inner chamber, and a central port 123 is the outlet from the inner chamber. The mid-port 122 can be used to bypass one or other of the outer or inner chambers, or it may be closed to connect the two chambers in series.




FIG. 3




FIG. 4

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

BEST AVAILABLE COPY

GB 2 358 438 A




FIG. 1




FIG. 2




FIG. 3




FIG. 4

MULTI-STAGE SCROLL COMPRESSOR

This invention relates to scroll compressors, and in particular to a multi-stage scroll compressor having more than one discharge pressure, and which can operate as a compressor or as a vacuum pump.

Many pneumatic applications require combinations of discharge pressures. Such combinations include, for example, pressure and vacuum, pressures at two or more discharge pressures, and higher pressures requiring two or more stages. Applications where such combinations are currently required include pneumatic controls for heart balloons which require pressure and vacuum, and refrigerant recovery systems which require high pressures for the recovery of refrigerant and a vacuum for evacuating the refrigerant system before charging of the system. In systems which require high pressures, such as refrigerant recovery systems, it is generally beneficial to have a two stage compressor and a vacuum pump.

It is presently common to separate the compressor and vacuum functions. For example, a separate compressor and vacuum pump are used in refrigerant recovery. One is used to recover the refrigerant and another unit is used to evacuate the system. The pneumatic controls for heart balloons include a compressor mounted to one end of the motor and a vacuum pump mounted to the opposite end. The compressor will then fill the balloon and the

compressor will deflate the balloon. In multi-stage applications, more than one pumping unit is typically employed.

The use of two units adds cost and complexity to devices, such as those noted above. It would be beneficial if the two functions could be incorporated into a single device.

A scroll of the present invention can be operated as either a vacuum pump, a low pressure compressor or a high pressure compressor. The scroll includes a housing, a fixed scroll plate having a continuous fixed involute wrap and an orbiting scroll plate having a continuous orbiting involute wrap. The wraps are of constant width and pitch. The fixed and orbiting scroll plates are mounted in the housing with their involute wraps extending toward each other to define a series of chambers. The fixed involute wrap and orbiting involute wrap each have at least a first section of one height and a second section of a second different height. Additionally, the scroll includes a first port proximate a peripheral edge of the housing, a second port proximate the center of the housing, and at least one mid-port; the mid-port being located proximate the change in height between the first and second sections of the involute wraps.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a sectional view of a multi-stage scroll-compressor of the present invention;

FIG. 2 is a sectional view of the scroll-compressor taken along line 2—2 of FIG. 1;

FIG. 3 is a sectional view of a second embodiment of the scroll-compressor; and

FIG. 4 is a sectional view of the scroll-compressor taken along line 4—4 of FIG. 3.

Corresponding reference numerals will be used throughout the several figures of the drawings.

The following detailed description illustrates the invention by way of example and not by way of limitation. This description will clearly enable one skilled in the art to make and use the invention, and describes several embodiments, adaptations, variations, alternatives and uses of the invention, including what I presently believe is the best mode of carrying out the invention.

The scroll-compressor 1 includes a housing 3 which encloses a fixed involute plate 5 and an orbiting involute plate 7. Each plate includes an involute wrap 9 and 11, respectively. As seen in FIG. 2, the wraps 9 and 11 are continuous spirals. However, the wraps are dividable into outer sections 9a, 11a and 9b, 11b. The outer wrap sections 9a and 11a have a different height than the inner wrap sections 9b and 11b. As shown in FIG. 1, the wrap sections 9a and 11a are taller than the wrap sections 9b and 11b. The wrap sections 9a, 9b and 11a, 11b are continuous. That is, there is no break between wrap section 9a and 9b or between wrap section 11a and 11b. Additionally, the wall thickness and pitch is maintained at a constant desired thickness and pitch throughout the entire length of the wraps 9 and 11. The scroll-compressor includes a pair of ports 22 at the diameter where the change in height occurs. Thus, the only difference is that the outer wraps 9a, 11a define chambers 15a which are taller than the chambers 15b defined by the inner wrap sections 9b, 11b.

As seen in FIG. 1, the orbiting involute plate 7 includes a generally flat plate 17 from which the wrap 9 extends. The fixed plate 5, on the other hand, includes an outer annular

section 19 and an inner section 21, from which the wrap sections 9a and 9b depend from, respectively. The two sections 19 and 21 of the plate 5 are spaced axially from each other. In FIG. 1, to accommodate the shorter wrap sections 9b, the inner section 21 of plate 5 is axially closer to the orbiting plate than is the outer section 19. Thus, as noted above, the outer chambers 15a are taller than the inner chamber 15b. Therefore, the percentage change in pressure between the entrance and exit to the outer wraps is less than the percentage change in the pressure between the entrance and exit to the inner wraps.

The scroll compressor 1 includes three sets of ports. It has inlet ports 21 at the entrance of the outer wrap sections 9a and 11a, mid-ports 22 at the change between the wrap sections (i.e., where the wrap height changes), and outlet ports 23 at the center of the compressor. The mid-ports 22 are the exit from the outer section and the entrance to the inner section of the involute wraps.

The scroll compressor 101 shown in FIGS. 3 and 4 is just the opposite of the scroll compressor 1 of FIGS. 1 and 2. In the scroll compressor 101, the outer sections 109a and 111a of wraps 109 and 111 are shorter than the inner sections 109b and 111b. It also has three ports, an inlet port 121, a mid-port 122, and a central outlet port 123. The inlet port 121 is the inlet to the outer section of the compressor; the mid-port 122 is both the outlet to the outer section and the inlet to the inner section, and the central port 123 is the outlet from the inner section.

The pressure ration of the inner and outer sections of the compressors 1 and 101 are independent of each other, and are determined by the number of spiral wraps in each section. The only requirement is that the discharge (or outlet) pressure of the outer section be equal to the inlet pressure of the second (or inner section) or stage.

Thus, if the scroll-compressor were to be operated as a combination pressure and vacuum pump, the inlet 121 of compressor 101 (FIGS. 3 and 4) would be connected to a vacuum source; the mid-port would be open to the atmosphere; and the outlet or discharge port 123 would be connected to a pressure source.

If the unit were to be used with refrigerant recovery where displacement is relatively low, but the pressure ratio can be high, the outer stage would be bypassed and only the inner stage would be used for recovery. Thus, the mid-ports would be used as the inlet to the compressor. For system evacuation, the outer stage, which has a large displacement would be used for achieving a rough vacuum quickly and the inner stage would be by-passed. To achieve higher vacuums, the outer and inner stages would be connected in series by closing the mid-port. This would result in a two stage vacuum pump.

As can be appreciated from a review of the foregoing specification, the scroll-compressor of the present invention produces two different compression processes on the same scroll. This is facilitated by the mid-ports 22 and 122. The provision of the mid-ports 22 and 122, in association with the involute wraps 9, 11, 109 and 111, allows for a single scroll to be used as a vacuum pump, a low pressure compressor, or a high pressure compressor, depending on how the outer port, mid-port, and inner port are utilized.

In view of the above, it will be seen that the advantages of the present invention have been achieved and other advantageous results have been obtained. As various changes could be made in the above constructions without departing from the scope of the invention, it is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense. Although only two

stages are shown, more stages could be employed. Thus, the scroll compressor could have three, four or more stages. There would be a mid-port for each stage, to allow for various stages to be by-passed, connected in series, or open to the atmosphere, as may be desired for a particular function.

CLAIMS:

1. A scroll which can be operated as either a vacuum pump, a low pressure compressor or a high pressure compressor; the scroll including a housing, a fixed scroll plate having a continuous fixed involute wrap and an orbiting scroll plate having a continuous orbiting involute wrap; the fixed and orbiting scroll plate being mounted in the housing with the involute wraps extending toward each other to define a series of chambers; the fixed involute wrap and orbiting involute wrap each having at least a first section of one height and a second section of a second different height; the scroll further including a first port proximate a peripheral edge of the housing, a second port proximate the center of the housing, and at least one mid-port; the mid-port being located proximate the change in height between the first and second sections of the involute wraps.
2. The scroll of claim 1 wherein the wraps are of constant width and pitch.
3. The scroll of claim 1 wherein the first section of the wraps is taller than the second section of the wraps; the first wrap sections surrounding the second wrap sections.
4. The scroll of claim 1 wherein the first section of the wraps is shorter than the second section of the wraps; the first wrap sections surrounding the second wrap sections.



Application No: GB 0001150.2
Claims searched: 1 to 4

Examiner: Robert Crowshaw
Date of search: 20 June 2000

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK Cl (Ed.R): F1F (FAA, FD, FEQ, FEV, FEW)
Int Cl (Ed.7): F01C 1/02; F04C 2/02, 18/02
Other: Online databases: EPODOC, JAPIO, WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
Y	GB 2002455 A (INGERSOLL-RAND) Note the vent port 50 and re-entry port 54 between inlet and outlet ports 48,56 in figures 5 & 6.	1-4
Y	EP 0728947 A1 (SBPV) Note the different height wraps 24,25,34,35 in figure 1.	1-3
Y	US 4477238 (SANDEN) Note the height H1 of the taller wrap which surrounds the wrap of height H2 in figure 3.	1-3
Y	US 4457674 (SANDEN) Note the height H2 of the shorter wrap which surrounds the wrap of height H in figure 3.	1, 2, 4

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.